

# MATERIAL SAFETY DATA SHEET

## 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Name: **NATCEM AC.**  
Application: As a Concrete Repair material, fast setting Mortar and Concrete  
Company: **Natural Cement Distribution Ltd.,**  
Address: 15 Fountain Parade, Off Spark Lane, Mapplewell, Barnsley. S75 6FW  
Telephone: 01226 381133/381155 Fax 01226 381177 www.naturalcement.co.uk

## 2: COMPOSITION AND INFORMATION ON INGREDIENTS

Composition **NATCEM AC** is a mix of Natural Cement and sand. By its nature, it can vary slightly in composition. Like Artificial Portland Cements it is composed of Calcium Aluminates and Silicates, with small Quantities of Lime and Magnesium, plus sulphates of Sodium, potassium and Calcium.

## 3: HAZARDS IDENTIFICATION

As Powder	Irritant (XI).	<b>NATCEM AC</b> contains a very fine powder. It should not be allowed to come into contact with the eyes. Risk Phrases R36, R37, R36
During Hydration	Irritant (XI).	As with all cements, <b>NATCEM AC</b> releases a strong alkali when it comes into contact with water (Hydration), including the mucous membranes of the nose, mouth and eyes. This alkali may occasionally cause burns or irritation. There is a possibility of an allergic reaction in hypersensitive individuals to salts of trace elements Chromium, formed during Hydration. Risk Phrases R41, R43. Avoid prolonged contact with wet Paste, Mortar or Concrete. Upon Hydration (After Mixing with water) a little heat is released. This is not a dangerous level.

## 4: FIRST AID

As Powder	Eye Contact	Irrigate immediately and profusely with clean water, to eliminate all trace of the powder.
	Skin Contact	Wash immediately and profusely with Soap and Water.
	Inhalation	Remove subject into fresh air until symptoms subside.
	Ingestion	Give plenty of water to drink. If symptoms persist, seek medical attention.
	As Hydrated Cement	In the event of a burn or irritation, wash the area thoroughly with cold water and seek medical advice.

## 5: FIRE FIGHTING MEASURES

NATCEM AC is not flammable. (UN. Class MO), nor will it facilitate the combustion of other materials.

## 6: ACCIDENTAL RELEASE

As powder Measures

Avoid Breathing the powder or dust.  
Clean up powder spillage with brush or vacuum cleaner, taking care not to raise excessive dust.

As hydrated

Allow to set before cleaning up cement

## 7: HANDLING & STORAGE

Packing

NATCEM AC is normally packed in a polythene bag with a resealable tie within a stitch sealed woven polypropylene outer

Safety

Avoid spillage from broken bags.  
Avoid raising dust while sweeping.  
Wear suitable protective clothing when handling bags, which may have small amounts of material on the outside.

Storage

Store in dry conditions.

## 8: EXPOSURE CONTROL

As powder

No specific data is available, but exposure tolerances would be greater than those for Portland Cement: 10mg/M3 total inhalable dust, 5mg/M3 respirable dust. 8 Hr TWA

Personal Protection

Avoid breathing the powder  
Avoid raising dust  
WEAR SAFETY GOGGLES, WORK GLOVES and DUST MASK

When Mixing

Always add the powder to the water in order to avoid raising dust.  
WEAR SAFETY GOGGLES and WATERPROOF GLOVES

When Working

Discard immediately any clothing that becomes saturated with wet cement.  
Avoid contact with the wet mortar, concrete or grout during the setting reaction. WEAR WATERPROOF GLOVES. Discard immediately any clothing that becomes saturated with wet cement.

## 9: PHYSICAL AND CHEMICAL

Appearance

Beige Grey Powder

Ph value

12 to 13 in water

Apparent Density	1.0
True	2.7
Solubility in water.	The dissolution is accompanied by the precipitation of the hydrates formed, i.e. On contact with water <b>NATCEM AC</b> part dissolves, combines with the water and sets hard. Setting Time is 35 mins at 20°C.

## 10: STABILITY AND REACTIVITY

**NATCEM AC** Is stable and inert when set, and as a DRY powder

## 11: TOXICOLOGY INFORMATION

**NATCEM AC** Is not toxic.  
 In the case of prolonged contact while setting, **NATCEM AC** can cause desiccation of the skin and/or mucous membranes.  
 When the setting reaction is occurring, certain salts of trace (e.g. Chromium) can cause an allergic reaction to the skin of certain individuals after long or repeated contact.

## 12: ECOLOGICAL INFORMATION

**Manufacture** **NATCEM AC** is manufactured in plant equipped with filters preventing emission of dust to the atmosphere. **NATCEM AC** is transported pneumatically within the plant to avoid dust emissions.

**In use** After setting and hardening, **NATCEM AC's** mortars, concretes and grouts are insoluble and stable.

## 13: DISPOSAL CONSIDERATIONS

**As Powder** Unused **NATCEM AC** should be set with water before disposal.

**As Paste, Mortar or Concrete.** Once set **NATCEM AC** is inert, non-toxic, non-biodegradable, and will not affect drinking water.

**General** Disposal should always comply with local, National and/or EC regulations.

## 14: TRANSPORT INFORMATION

**NATCEM AC** Requires no special precautions.

## 15: REGULATORY INFORMATION

### NATCEM AC

Is not subject to regulatory legislation.  
This SAFETY DATA SHEET supplements, but does not replace, other information given regarding the use of **NATCEM AC**.

The user bears the responsibility to ensure that **NATCEM AC** is used only in accordance with our instructions for the purposes intended.

Risk Phrases applicable to the powder.

R36 Irritant to Eyes.

R37 Instant to Respiratory System.

R38 Irritant to Skin.

Risk Phrases applicable during hydration

R41 Risk of serious damage to Eyes.

R43 May cause sensitisation by skin contact.

Safety Phrases

S2 Keep out of reach of Children

S22 Do not breath dust.

S24 Avoid contact with skin.

S26 In case of contact with Eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of soap and water.

S36 Wear suitable protective clothing

S37 Wear Suitable Clothing

S39 Wear eye and face protection.

## 16: OTHER INFORMATION

Further advice and information regarding the handling of cement products generally is available from:-

### **Natural Cement Distribution Ltd**

**Unit 12, Redbrook Business Park, Wilthorpe Road, Barnsley, South Yorkshire. S75 1JN**

**TEL: 01226 299333**

**Fax: 01226 299777**

**[www.naturalcement.co.uk](http://www.naturalcement.co.uk)**

CONTAC Health Hazard Information Sheet No- 26 (Cement)

Health and Safety at Work Act 1974 Control of Substances Hazardous to Health (Regulations) 19%

Portland Cement Dust - Criteria Document for an Occupational Exposure Limit. H.S.E. Guidance Note EH 26

H.S.E. Leaflet MS(B)G

H.S.E. Guidance Note EH40

Manual Handling Operations Regulations 1992

Chemicals (Hazard Information and Packaging) Regulations 1993

This SAFETY DATA SHEET is compiled in the full state of our current knowledge of the product in MAY 1995, and is subject to revision without notice. Users should ensure that they are aware of the latest revisions.